

# CAMSO MPT 552



MINI-DUMPERS



CONCRETE  
MIXERS



TELEHANDLERS



## A SMOOTH RIDE WITH ENHANCED TRACTION

Provides versatility and durability in off-road applications.  
Reduces vibrations for enhanced driving comfort while providing excellent traction in off-road conditions

[camso.co](http://camso.co)

## PERFORMANCE

TYRE LIFE




PUNCTURE RESISTANCE



TRACTION



# CAMSO MPT 552



### VERSATILE DIRECTIONAL TREAD PATTERN WITH CENTRE BLOCK

- Reduces vibrations and enhances driving comfort

### SELF-CLEANING STEPPED TREAD

- Maximizes cleanout for improved off-road traction



### OPEN SHOULDER TREAD DESIGN

- Provides excellent traction in off-road conditions

### IMPROVED HEEL ENGINEERING

- Reduces mounting and inflation time

TYRE SIZE	PR	RIM SIZE		ACTUAL TYRE DIMENSIONS					LOAD INDEX	SPEED SYMBOL	APPLICATION	INFLATION PRESSURE [bar] [PSI]	MAXIMUM TYRE LOAD [kg] [lb]				
		Recom-mended	Alter-native	O.D. [mm] [in]	O.W. [mm] [in]	O.T.D. [mm] [32 <sup>nd</sup> ] [in]	S.L.R. [mm] [in]	R.C. [mm] [in]					Static	10 km/h 6 mph	25 km/h 16 mph	40 km/h 25 mph	50 km/h 31 mph
10.0/75-15.3 IMP (255/75-15.3)	12	9.00	-	772	261	21	362	2328	126	A8	FREE ROLLING	4.70	2805	2380	2025	1700	1530
				30.4	10.3	26	14.3	91.7				68	6185	5245	4465	3750	3375
				772	261	21	362	2328	114	A8	DRIVE	4.70	2775	1650	1405	1180	1060
				30.4	10.3	26	14.3	91.7				68	6120	3640	3095	2600	2335
10.0/75-15.3 IMP (255/75-15.3)	18	9.00	-	763	264	20	359	2301	137	A8	FREE ROLLING	7.10	3795	3220	2735	2300	2070
				30.0	10.4	25	14.1	90.6				103	8365	7100	6030	5070	4565
				763	264	20	359	2301	124	A8	DRIVE	7.10	3760	2240	1905	1600	1440
				30.0	10.4	25	14.1	90.6				103	8290	4940	4200	3525	3175
11.5/80-15.3 IMP (295/80-15.3)	14	9.00	-	856	293	19	397	2582	139	A8	FREE ROLLING	4.75	4010	3400	2890	2430	2185
				33.7	11.5	24	15.6	101.7				69	8840	7495	6370	5355	4815
				856	293	19	397	2582	126	A8	DRIVE	4.75	3995	2380	2025	1700	1530
				33.7	11.5	24	15.6	101.7				69	8805	5250	4465	3750	3375
12.0/75-18 IMP (300/75-18)	12	W9	9; 11	915	298	19	427	2748	139	A8	FREE ROLLING	4.00	4010	3400	2890	2430	2185
				36.0	11.7	24	16.8	108.2				58	8835	7495	6370	5355	4820
				915	298	19	427	2748	126	A8	DRIVE	4.00	3995	2380	2025	1700	1530
				36.0	11.7	24	16.8	108.2				58	8805	5250	4465	3750	3375

Higher load capacities may be allowed for cyclic loaded (HLV) applications with a one way distance of maximum 1 km. Contact our technical department for more information. All tyres listed are tubeless.

AUTHORIZED DISTRIBUTOR:

camso.co



FORMERLY CAMOPLAST SOLIDEAL