

MAGNA TYRES GROUP

PORTHANDLING



MAGNA MBO2 IND4

12.00-24

14.00-24

16.00-25

18.00-25

Get all the benefits of Magna Technology!

- Self cleaning and non-directional tread pattern
- High reliability and long tread life
- Excellent traction



Cross Plyed Construction - Multifunctional

MAGNA MB02

PORTHANDLING PORTHANDLING PORTHANDLING


Magna MB02 is designed for use on container handlers.

Side wall protection and flotation are enhanced by the wide shoulder design.

The tread compound provides excellent performance against cutting and abrasion.




Improved traction and performance through non-directional tread design.



All cross ply construction. Improved protector plies optimize load performance and operator comfort.



New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	Pattern	TRA code	Ply rating	Standard rim	Overall diameter (mm)	Section width (mm)	Tread depth (mm)	Inflation pressure (bar)	Load capacity (kg)			
									25 km/h	10 km/h	5 km/h	Static
12.00-24	MB02	IND4	20	8.50	1247	315	35	9.5	6500	8500	9900	11400
14.00-24	MB02	IND4	24	10.00	1370	375	50	10.0	8200	11200	12200	13200
16.00-25	MB02	IND4	32	11.25/2.0	1495	430	50	10.5	15600	16900	18100	22500
18.00-25	MB02	IND4	40	13.00/2.5	1673	515	55	10	21200	22900	24600	30600

Magna Tyres Group
P.O. Box 436
5140 AK Waalwijk
The Netherlands

Magna Tyres Group
Elzenweg 7
5144 MB Waalwijk
The Netherlands

Phone: +31 416 675 220
Fax: +31 416 675 221
Email: info@magnatyres.com
www.magnatyres.com

