

MAGNA TYRES GROUP

EARTHMOVER



MAGNA MB300 E3/L3

Get all the benefits of Magna Bias Tyre Technology!

- Self cleaning and non-directional tread patterns
- High reliability and long tread life
- Excellent traction



Cross Plyed Construction - Multifunctional

MAGNA MB300

EARTHMOVER


MAGNA TYRES develops and manufactures high quality tyres for construction and mining purposes, especially designed for the most severe applications.

MB300 regular tread is designed with a specially compounded rubber to resist cutting and wearing, as well as overheating.


Designed for operating on rock, coal and earth surfaces.



Improved traction and performance through deep non-directional tread design.



All cross ply construction. Improved protector plies optimize load performance and operator comfort.



New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	TT/TL	Ply	Tread	Pattern	Pressure (kpa)	Loading capacity (kg)	Pressure (kpa)	Loading capacity (kg)	O.D. of inflation (mm)	Section width (mm)	Standard Rim
		Rating	Pattern	No.							
14.00-24	TT/TL	24	L-3	MB300	850	9500	575	5150	1370	375	10.0
14.00-24	TT/TL	28	L-3	MB300	926	10000	650	5600	1370	375	10.0
16/70-20	TT/TL	10	L-3	MB300	325	4200	250	2400	1075	410	13.00
16/70-20	TT/TL	16	L-3	MB300	450	5150	350	2925	1175	410	13.00
16/70-24	TT/TL	10	L-3	MB300	325	4750	250	2775	1175	410	13.00
16/70-24	TT/TL	14	L-3	MB300	450	5650	350	3375	1175	410	13.00
16.00-24	TT/TL	16	L-3	MB300	425	8520	325	4875	1490	430	11.25/2.0
16.00-24	TT/TL	24	L-3	MB300	650	10600	475	6000	1490	430	11.25/2.0
15.5-25	TT/TL	12	L-3	MB300	400	5600	250	3250	1275	395	12.00/1.3
15.5-25	TT/TL	16	L-3	MB300	550	7050	300	3750	1275	395	12.00/1.3
17.5-25	TT/TL	12	E-3/L-3	MB300	350	6150	225	3650	1350	445	14.00/1.5
17.5-25	TT/TL	16	E-3/L-3	MB300	475	7300	300	4250	1350	445	14.00/1.5
17.5-25	TT/TL	20	E-3/L-3	MB300	575	8520	400	5000	1350	445	14.00/1.5
18.00-25	TT/TL	28	E-3	MB300	650	13600	500	8000	1615	495	13.00/2.5
18.00-25	TT/TL	32	E-3	MB300	750	15000	575	8750	1615	495	13.00/2.5
18.00-25	TT/TL	40	E-3	MB300	950	17000	700	9750	1615	495	13.00/2.5
20.5-25	TT/TL	16	E-3/L-3	MB300	350	8520	275	5450	1490	520	17.00/2.0
20.5-25	TT/TL	20	E-3/L-3	MB300	450	9500	325	6000	1490	520	17.00/2.0
23.5-25	TT/TL	16	E-3/L-3	MB300	300	9500	225	6150	1615	595	19.50/2.5
23.5-25	TT/TL	20	E-3/L-3	MB300	375	10900	300	7300	1615	595	19.50/2.5
23.5-25	TT/TL	24	E-3/L-3	MB300	475	12500	350	8000	1615	595	19.50/2.5

Magna Tyres Group
P.O. Box 436
5140 AK Waalwijk
The Netherlands

Magna Tyres Group
Elzenweg 7
5144 MB Waalwijk
The Netherlands

Phone: +31 416 675 220
Fax: +31 416 675 221
Email: info@magnatyres.com
www.magnatyres.com

