



AGRICULTURE  
**MAGNA**  
**AG01**  
**65-SERIES**

**MAGNA AG01 65-SERIES**

Flexible casing provides soil protection and increased ride comfort for the driver.

Wide lugs improve service life and also enhances stability and manoeuvrability on both soft and muddy surfaces.



Tread designed to offer superior traction, self-cleaning and reduced fuel consumption.



Wider footprint by high flexing casing improving soil and crop protection.



Radial construction offers optimized load performance, driveability and operator comfort.



Tyre size	Pattern	Max. speed	Load/ Speed Index	Single max load/ pressure	Overall diameter (mm)	Section width (mm)	Tread depth (mm)	Rim	Tyre Weight
		(km/h)							
540/65R24	AG01	40	140A8	2500kg/1.6 bar	1312	550	48	W18L/DW18L	110
		50	137B	2300 kg/1.6 bar					
480/65R28	AG01	40	136A8	2240 kg/1.6 bar	1335	479	48	W15L/DW16L	101
		50	133B	2060 kg/1.6 bar					
540/65R28	AG01	40	142A8	2650 kg/1.6 bar	1413	550	51	W18L/DW18L	133
		50	139B	2430 kg/1.6 bar					
540/65R30	AG01	40	143A8	2725 kg/1.6 bar	1464	550	51	W18L/DW18L	142
		50	140B	2500 kg/1.6 bar					
540/65R34	AG01	40	145A8	2900kg/1.6 bar	1566	550	48	W18L/DW18L	140
		50	142B	2650 kg/1.6 bar					
540/65R38	AG01	40	147A8	3075kg/1.6 bar	1667	550	48	W18L/DW18L	155
		50	144B	2800 kg/1.6 bar					
600/65R34	AG01	40							
		50							
600/65R38	AG01	40							
		50							
650/65R38	AG01	40							
		50							

**UNDER DEVELOPMENT**

**UNDER DEVELOPMENT**

**UNDER DEVELOPMENT**



**Magna Tyres Group**

P.O. Box 436, 5140 AK Waalwijk, The Netherlands  
 Elzenweg 7, 5144 MB Waalwijk, The Netherlands

Phone: +31 416 820 036, Fax: +31 416 820 037  
 Email: info@magnatyres.com, www.magnatyres.com

