



AGRICULTURE  
**MAGNA  
AG01  
70-SERIES**

**MAGNA AG01 70-SERIES**

Flexible casing provides soil protection and increased ride comfort for the driver.

Wide lugs improve service life and also enhances stability and manoeuvrability on both soft and muddy surfaces.



Tread designed to offer superior traction, self-cleaning and reduced fuel consumption.



Wider footprint by high flexing casing improving soil and crop protection.



Radial construction offers optimized load performance, driveability and operator comfort.



Tyre size	Pattern	Max. speed (km/h)	Load/ Speed Index	Single max load/ pressure	Overall diameter (mm)	Section width (mm)	Tread depth (mm)	Rim	Tyre Weight
380/70R24	AG01	40	125A8	1650 kg/1.6 bar	1190	380	46	W12	69
		50	123B	1550 kg/1.6 bar					
420/70R24	AG01	40	130A8	1900 kg/1.6 bar	1248	418	48	W13	83
		50	127B	1750 kg/1.6 bar					
420/70R28	AG01	40	133A8	2060 kg/1.6 bar	1349	418	47	W13	97
		50	130B	1900 kg/1.6 bar					
480/70R28	AG01	40	140A8	2500 kg/1.6 bar	1421	479	49	W15L/DW15L	117
		50	137B	2300 kg/1.6 bar					
520/70R38	AG01	40	150A8	3350 kg/1.6bar	1749	516	51	W16L/DW16L	172
		50	147B	3075 kg/1.6 bar					
580/70R38	AG01	40	155A8	3875 kg/1.6 bar	1827	577	50	W18L/DW18L	189
		50	152B	3550 kg/1.6 bar					
710/70R38	AG01	40							
		50							

**UNDER DEVELOPMENT**



**Magna Tyres Group**

P.O. Box 436, 5140 AK Waalwijk, The Netherlands  
Elzenweg 7, 5144 MB Waalwijk, The Netherlands

Phone: +31 416 820 036, Fax: +31 416 820 037  
Email: info@magnatyres.com, www.magnatyres.com

