



AGRICULTURE
MAGNA
AG01
85-SERIES

MAGNA AG01 85-SERIES

Flexible casing provides soil protection and increased ride comfort for the driver.

Wide lugs improve service life and also enhances stability and manoeuvrability on both soft and muddy surfaces.



Tread designed to offer superior traction, self-cleaning and reduced fuel consumption.



Wider footprint by high flexing casing improving soil and crop protection.



Radial construction offers optimized load performance, driveability and operator comfort.



Tyre size	Pattern	Max. speed (km/h)	Load/ Speed Index	Single max load/ pressure	Overall diameter (mm)	Section width (mm)	Tread depth (mm)	Rim	Tyre Weight
280/85R24 (11.2R24)	AG01	40	115A8	1215 kg/ 1.6 bar	1086	282	41	W10	46
		50	112B	1120 kg/1.6 bar					
340/85R24 (13.6R24)	AG01	40	125A8	1650 kg/1.6 bar	1190	345	44	W12	65
		50	122B	1500 kg/1.6 bar					
380/85R24 (14.9R24)	AG01	40	131A8	1950 kg/ 1.6 bar	1258	388	46	W13	80
		50	128B	1800 kg/1.6 bar					
320/85R28 (12.4R28)	AG01	40	124A8	1600 kg/ 1.6 bar	1255	319	42	W11	65
		50	121B	1450 kg/1.6 bar					
420/85R28 (16.9R28)	AG01	40	139A8	2430 kg/1.6 bar	1443	438	48	W15L	102
		50	136B	2240 kg/1.6 bar					
420/85R30 (16.9R30)	AG01	40	140A8	2500 kg/1.6 bar	1480	435	48	W15L	111
		50	137B	2300 kg/1.6 bar					
420/85R34 (16.9R34)	AG01	40	142A8	2650 kg/1.6 bar	1575	430	48	W15L	118
		50	139B	2430 kg/1.6 bar					
420/85R38 (16.9R38)	AG01	40	144A8	2800 kg/1.6 bar	1679	418	46	W14L	128
		50	141B	2575 kg/1.6 bar					
520/85R38 (20.8R38)	AG01	40	155A8	3875 kg/1.6 bar	1841	527	50	W18L	185
		50	152B	3550 kg/1.6 bar					



Magna Tyres Group

P.O. Box 436, 5140 AK Waalwijk, The Netherlands
 Elzenweg 7, 5144 MB Waalwijk, The Netherlands

Phone: +31 416 820 036, Fax: +31 416 820 037
 Email: info@magnatyres.com, www.magnatyres.com

