

# CAMSO TM R4



COMPACT  
WHEEL LOADERS



## DURABLE OFF-ROAD PERFORMANCE

Provides incomparable durability and traction for heavy-duty applications. Enhanced tread cleanout and lug stability combined to maximize performance.

[camso.co](http://camso.co)

## PERFORMANCE

TIRE LIFE




PUNCTURE RESISTANCE



TRACTION



# CAMSO TM R4



## HAULER STEPPED TREAD DESIGN

- Enhances tread cleanout for improved traction

## OPTIMIZED LUG-TO-VOID RATIO

- Enhances longevity and tread puncture resistance



## HEAVY-DUTY CARCASS

- Provides excellent stability and side impact resistance

## TAPERED TREAD LUGS

- Improves lug stability for even wearing

TIRE SIZE	PR	RIM SIZE		ACTUAL TIRE DIMENSIONS			LOAD INDEX	SPEED SYMBOL	TRA CODE	APPLICATION	MAXIMUM TIRE LOAD [kg]							
											On other vehicles					On counterbalanced lift trucks		
											Inflation pressure [bar]	Creep	8 km/h	16 km/h	50 km/h	Inflation pressure [bar]	Load wheel	Steering wheel
18-19.5	16	14x19.5	-	1117	454	32	160	A8	R-4	DRIVE	4.50	9090	6300	5985	4050	5.50	6435	5400
405/70-20 (16/70-20)	14	13x20	13SDC	1085	403	27	154	A8	R-4	FREE	3.50	6190	5250	4990	3375	5.50	5365	4500
				1085	403	27	142			DRIVE	3.50	6230	3710	3525	2385	5.50	5365	4500
18-22.5	16	14x22.5	-	1209	444	35	163	A8	R-4	DRIVE	4.50	9850	6825	6485	4390	5.50	6970	5850
400/80-24 (15.5/80-24)	16	13x24	13SDC	1244	411	37	156	A8	R-4	CONSTANT	4.00	6190	5250	4990	3375	-	-	-
				1244	411	37	156			CYCLIC	4.00	6230	3710	3525	2385	-	-	-
400/80-24 (15.5/80-24)	20	13x24	13SDC	1238	409	37	162	A8	R-4	CONSTANT	5.00	10925	5940	5370	4560	-	-	-
				1238	409	37	162			CYCLIC	5.00	10925	7125	6365	4560	-	-	-
440/80-24 (16.5/85-24)	22	DW14Lx24	DW13 DW13L DW15L	1328	453	33	168	A8	R-4	CONSTANT	5.00	12880	7000	6330	5375	-	-	-
				1328	453	33	168			CYCLIC	5.00	12880	8400	7505	5375	-	-	-

## IMPROVED MOUNTABILITY



Increased tension on rim prior to inflation compared to competition designed to prevent air leakage during inflation process.

AUTHORIZED DISTRIBUTOR:

[camso.co](http://camso.co)



FORMERLY CAMOPLAST SOLIDEAL