

# MULTI TOUGH

Home / CONSTRUCTION & INDUSTRIAL / MULTI TOUGH

Print this Page Print Certificate



GALAXY | CONSTRUCTION & INDUSTRIAL

## MULTI TOUGH



This radial tire is used for mixed application on hard surfaces and soft soil. The unique non-directional tread design is ideal for on and off-the-road service and facilitates easier self-cleaning. High mileage, best traction, fuel saving and ride comfort are some of the tire's advantages.



**Tire Size** 500/70R24



Backhoe



Utility Tractor



Compact Wheel Loader



Telehandler



Special Compound



Wear Resistant Compound

[Send an enquiry](#)

## REAR BACKHOE - 500/70R24

International Standard (mm – bar - kg - kmph)

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
		SW mm	OD mm					Speed						
								Constant load				Cyclic Applications		
							Static kmph	25 kmph	30 kmph	40 kmph	50 kmph	10 kmph	15 kmph	
500/70R24	DW16L DW15L DW18L	503	1311	584	3810	<b>157A8</b>	1	4810	2220	2170	2090	1900	3140	2800
							1.4	5840	2690	2640	2540	2310	3810	3400
							1.8	6760	3120	3060	2940	2680	4410	3940
							2	7200	3320	3260	3130	2850	4700	4190
							2.4	8000	3690	3620	3480	3170	5220	4660
							2.8	8760	4040	3960	3810	3470	5720	11260
							3	9130	4210	4130	3970	3610	5960	5320
							3.2	9490	4370	4290	4125	3750	6190	5530